Installation Sheet KSR7270-74

Mika LED Pendant fitting with Shade

Read these instructions before commencing installation. Please give these instructions to the owner/occupier after installation to retain for future reference/maintainence.

IP20 0.3m 240VAC~50Hz 9W LED

These fittings are Class I and must be Earthed

Available Finishes: White with White Shade (KSR7270), White with Transparent Shade (KSR7271), Black with Smoked Transparent Shade (KSR7272), Black with Black/Gold Shade (KSR7273) and Aluminium with Transparent Shade (KSR7274)

Important Information

It is recommended that these luminaires are installed and fitted by a qualified electrician ensuring the installation complies with current IEE wiring regulations & local building control. These products are designed for connection to a 240V~50Hz supply.
Any faulty, broken or damaged luminaires should be replaced immediately.
KSR will not accept responsibility for any claims arising from a poor installation.
Please Note: The limited warranty shall be deemed null and void in the following circumstances: Failure by the installer, end user or any third party to exercise caution to protect any covered product or part from outside damage, adverse temperature (normal operating ambient temperature -10°C - +40°C), humidity conditions, fluctuations in the electrical system or physical abuse as well as failure related to workmanship in the installation of the products or parts.

Important User Advice

Always switch off mains supply before servicing.
Do not use Megger or similar high voltage instruments. Due to the fact this luminaire contains electronic components that maybe damaged by high test voltages, they must be disconnected from the circuit before testing.
To prevent damage to the driver, do not mix with conventional magnetic ballasts on the same electrical circuit.
At the end of life the luminaire is classed as WEEE under directive 2014/30/EU and should be disposed of in accordance with local legislation.

Installation Procedure

Familiarize yourself with the luminaire/installation procedure and ensure the power is safely isolated before installing the luminaire.

Identify a suitable area(s) for the pendant to be mounted in and ensure the surface being mounted onto is smooth and suitable for the product type
Release both screws at the base of the ceiling rose and loosen off just enough to allow the ceiling rose to rotate free of the mounting bracket see fig 1
With the mounting plate free, offer up the mounting bracket to the mounting surface and prepare ceiling for fixings provided
With fixing positions prepared fasten fixings onto mounting bracket until secure
Using the terminal block provided terminate wiring Brown to Live, Blue to Neutral and Green/Yellow to Earth ⏚
see fig 2
With terminations completed resecure ceiling rose onto mounting bracket ensuring no cables are pinched or nicked (fig 1).
Next remove the cover from the main pendant by unscrewing the cover and fit your chosen shade onto body. Replace cover and screw on shade until secure see Fig 3
Now Power on and Test Luminaire

Please note drop length of Pendant can be adjusted in the ceiling rose according to application, max drop length is 2700mm

Fig 1.




Fig 2.






Fig 3.





Lamp Details

Lamp: LED
Wattage: 9W
3000K 780lumen
CRI: Ra>82

The light source of this luminaire is not replaceable; when the light source reaches its end of life the light source and control gear shall be replaced

This product contains a light source of energy efficiency class F

KSR Lighting Aftersales: 023 92 674343
E-mail: aftersales@ksrlighting.com

KSR Lighting Ltd, Optimum House, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex, PO22 9TS.