

Description

Siena LED Wall Pack Luminaire, Complete with Integral Photocell.



General

Colour Options	Black with Opal Diffuser Only
Light Source	LED, Non Replaceable Module
LED Expected Life	30,000 Hours
Product Warranty	2 Years from Date of Purchase
Mounting Method	Wall Mount only

Electrical Parameters

Supply Voltage	100-240v AC
Frequency	50/60 Hz
Circuit Wattage	30W Including Driver
Circuit Current	0.40 Amps
Driver mA Rating	700mA
PFC	0.9
In Rush Current	0.60 Amps

Classifications and Approvals

Earth Class	Class I, Requires Earth
IK Rating	IK10
IP Rating	IP65
Efficiency Rated (Part L)	Yes
Energy Rating	A
CE Marked	Yes
Designed In Accordance to	BSEN60598, EM55015

Installation

Mounting Bracket	N/A
Cable Entry	20mm Drill Outs on Left/Right of Base & Rear
Method of Fix	Screw Fix to Suitable Surface
Working Ambient Temp.	-10°C to +40°C
Primary Connections	L, E & N Screw Down Terminals, Large 15Amp Connector
Secondary Connections	N/A
Accessories	N/A

Performance

Luminous Flux	2031 Lumens
Luminous Efficacy (L/pw)	68 L/pw
CCT	4000k
CRI (Ra)	Ra:83
Beam Angle	120°
Dimmable	No, Non Dimmable
Photocell Operating	50 lux on

Construction

Main Chassis	Polycarbonate
Trim/Bezel	Polycarbonate
Diffuser	Opal Polycarbonate
Lens	N/A
Heat Sink	Aluminium
Finish Type	Coloured Polycarbonate

