## Installation Sheet

### KSR7108/09

retain them for future reference. Read these instructions before commencing installation &

# IP55 ⊕ **( €** 240V 50W Max

# Important Information

the IEE wiring regulations BS7671. It is recommended that luminaires are installed by a qualified electrician The installation of this product must comply with the current edition of

installation KSR will not accept responsibility for any claims arising from a poor Any damaged parts should be replaced as soon as possible These products are designed for connection to a 240V 50Hz supply.

# Important User Advice

soapy water (no abrasive cleaners) and greasing all screws every 3 KSR recommends a maintenance schedule of washing down with Always switch off mains supply before installation or servicing.

### Installation Details

Remove the four retaining screws from the base of the wall light holding the back plate to the fitting.


the wiring terminals at the top. Secure the back plate to a suitable surface, dressing supply cable though the supplied blank grommet. Ensuring the cable entry is at the bottom with

base and/or the guide in Fig 1 as below. Wire the mains supply to the terminal black following the marking on the

Place the fitting back on to the base plate and secure with the four fixings cover the screw heads with the 4 silver caps provided. Insert a lamp, turn on the power and test


may distort the seals and cause moisture ingress Note: do not over tighten the glass lenses when installing the lamp as this
















155






### Sevas




### 🚺 ) ) Wall Light

Single & Twin GU10 Wall Light Anthracite Finish



### Base Plate



### Lamp Details

Light Source: GU10 Halogen or LED Lamp Wattage: 50W Max Lamp Not Included

E-mail: info@ksr-lighting.co.uk KSR Lighting Aftersales: 023 92 674343