

Acqua Wall Light

Exterior Bulkheads



Data Sheet

Product Information

The Acqua wall lights are available with PIR sensor making them ideal for external applications where presence detection is required for security and safety reasons.

Product Features

- 2 year warranty
- IP44
- Class II
- 8w 3000K LED
- Available to order with PIR sensor
- CRI: Ra82
- Not suitable for High Saline Areas
- L70 - 25,000hrs

Product Specification

Product Code	Product Description	Wattage (W)	CCT (K)	Lumens (lm)	CRI (Ra)	Energy Efficiency Class 2021	Protection Class
KSR9955	Acqua 8w 3000K LED Wall Light	8w	3000	250	82	G	II
KSR9956	Acqua 8w 3000K LED Wall Light with PIR Sensor	8w	3000	250	82	G	II

Nominal voltage	220~240VAC
Operating frequency	50Hz
Circuit Wattage	8w including driver losses
Circuit Current	0.03A
Driver mA Rating	150mA
PFC	0.75
In Rush Current	0.5A Max Peak
Ambient temperature range	-10°C to +30°C
IP rating	44

Construction

Body: 304 Stainless Steel
Lens: Opal Polycarbonate

Standards


BSEN60598-1:2021 Luminaires – Part 1: General requirements and tests

In Conformity with


LVD Low voltage directive 2014/35/EU
EMC Electromagnetic compatibility directive 2014/30/EU
ERP Energy related products directive 2019/2020/EU
RoHS Restriction of hazardous substances 2015/863/EU

Product Dimensions

KSR9955



KSR9956



KSR Lighting is constantly developing and improving its products. For this reason, all product descriptions in this data sheet are intended as a general guide, and KSR may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this data sheet present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, KSR Lighting cannot accept any liability arising from the reliance on such data to the extent permitted.