


# Seron LED Spotlight

**Exterior Recessed Lighting** 



#### **Product Information**

Seron LED Spotlights are ideal for lighting wall perimeters for Pathways, feature lighting and wall washing applications.

Available with an optional Visor attachment to help control the direction of the light source.

### **Product Features**

- 2 year warranty
- Class I
- IP65
- 8.5w 4000K LED
- Non-Dimmable
- Pre-wired with 500mm of Flex
- L70 30,000hr

# **Product Specification**

Product Code	Product Description	Wattage (W)	CCT (K)	Lumens (lm)	Energy Efficiency Class	Protection Class
KSR1325	Seron 8.5w LED 4000K LED Spike Light	8.5	4000	568 297 with Visor	G	I
KSR1326	Seron Visor Only for KSR1325					

Nominal voltage	220-240VAC		
Operating frequency	50Hz		
Circuit Wattage	8.2w including losses		
Circuit Current	0.019 A		
Driver Current rating	210mA		
PFC	0.61		
In Rush Current	0.25 A Max Peak		
Ambient temperature range	-10°c~+30°c		
Start time	< 0.5 sec		
IP rating	65		

#### **Construction**

Body: Cast Aluminium Lens: Transparent Glass

#### **Standards**

BSEN60598-1:2021 Luminaires – Part 1: General requirements and tests


## In Conformity with

LVD Low voltage directive 2014/35/EU


EMC Electromagnetic compatibility directive 2014/30/EU ERP Energy related products directive 2019/2020/EC RoHS Restriction of hazardous substances 2015/863/EU

#### **Product Dimensions**

#### KSR1325



#### KSR1325 with KSR1326



KSR Lighting is constantly developing and improving its products. For this reason, all product descriptions in this data sheet are intended as a general guide, and KSR may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this data sheet present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, KSR Lighting cannot accept any liability arising from the reliance on such data to the extent permitted.